


Independent Electric Rotary Table Driven Rig

Main Features

1. Based on general drilling mechanism, our independent electric drilling rig isolates rotary table from drawworks drive. Therefore, rotary table speed and torque as well as mud pump stroke can be practically adjusted in accordance with actual applications, which is the perfect foundation for customized drilling effects and automatic drilling system.
2. We adopt digital automatic control technology for rotary table and auto bit feeding system. Our drill machine offers similar performance as digital control variable frequency rig yet in a more cost effective manner.
3. Our independent electric drilling rig is endowed with touch screen so as to offer in-time adjustments on drilling parameters to fit actual applications. Operatives avail from drastically reduced work load and enhanced working efficiency. Moreover, value-added functions, such as parameter display, store, regulation and remote management, are also available to meet customer satisfaction.

3000m Independent Electric Rotary Table Driven Rig



Add.: No. 323, Shi Ji Avenue, Economic Development Zone, Chongzhou,
Chengdu City, Sichuan Province, China

Tel: +86-28-64367210 **Fax:** +86-28-64367210

Web: <http://www.cd-cobra.com> **E-mail:** cobracoltd@gmail.com

CHENGDU COBRA TRADING CO.,LTD

Specification

Nominal Drilling Depth	3000m (114mm Drilling Rod)	Substructure Type	Box on Box
	2500m (127mm Drilling Rod)	Substructure Height and Rotary Table Clearance	4.5m, 3.58m
Max. Hook Load	1700kN	Derrick Model and Effective Height	K-Shaped, 42m
Rope System of Travelling System	5×6, Successively Twined	Transmission Mode	Hydraulic Transmission + Chain Compound Gearbox +AC-VFD-AC
Rated Power of Drawworks	551kW (750hp) (600kW/800hp)	Main Diesel Engine Model/Power	2×810kW
Gear Number of Drawworks	4 Gears	Auxiliary Generator Quantity/Power	3×400kW
Diameter of Drilling Wire Rope	Φ29mm	Inverter-Duty Motor Quantity/Power	1×300kW + 1×22kW
Opening Diameter of Rotary Table	520.7mm (20 1/2")	High Pressure Mud Manifold	Φ102mm (Drift Diameter) × 35MPa
Gear Number of Rotary Table	1 Gear, Stepless Regulation	Effective Volume of Solid Control System	245m ³
Quantity and Power of Drilling Pump	1×1300hp (2×800hp/2×597kW)		

Add.: No. 323, Shi Ji Avenue, Economic Development Zone, Chongzhou,
Chengdu City, Sichuan Province, China

Tel: +86-28-64367210 Fax: +86-28-64367210

Web: <http://www.cd-cobra.com> E-mail: cobracoltd@gmail.com